

# Axpert MAX II TWIN Off-Grid Inverter

## Description



- Dual outputs, for smart load management
- Maximum PV input current increases to 27A
- Wide PV input voltage range 90VDC – 450VDC
- Status indication with RGB lights
- Built-in Wi-Fi for mobile monitoring (Android/iOS App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Compatible to Utility Mains or generator input
- Built-in anti-dust kit
- Built-in DC output for DC fan, LED bulb, router and so on.

Parallel operation with 6 units

## Axpert MAX II TWIN Off-Grid Inverter Selection Guide

MODEL	Axpert MAX II TWIN 8K	Axpert M
RATED POWER	8000VA/8000W	11000
PARALLEL CAPABILITY	YES, 6 units	
<b>INPUT</b>		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
<b>OUTPUT</b>		
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	230
Surge Power	16000VA	2
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Applia	
Waveform	Pure sine wave	
DC Voltage	12 VDC ± 5%, 100W	
<b>BATTERY</b>		
Battery Voltage	48 VDC	
Floating Charge Voltage	54 VDC	
Overcharge Protection	66 VDC	
<b>SOLAR CHARGER &amp; AC CHARGER</b>		
Solar Charger Type	MPPT	
Maximum PV Array Power	8000W (4000W x 2)	11000W
MPPT Range @ Operating Voltage	90 ~ 450 VDC	90
Maximum PV Array Open Circuit Voltage	500 VDC	5
Maximum PV Input Current	27A x 2 (MAX 40A)	
Maximum Solar Charge Current	150A	
Maximum AC Charge Current	120A	
Maximum Charge Current	150A	
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	158.4 x 503.6 x 530.8	
Net Weight (kgs)	20	
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact	
<b>OPERATING ENVIRONMENT</b>		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
<b>STANDARD</b>		
Compliance Safety	CE	

Product specifications are subject to change without further notice.